

Performance Data : Single Phase, 220 V, 50 Hz

Rated Output HP (kW)	No. of Poles	RPM (sync)	Frame Size/ Cons.	100 % Load			Breakaway I rated A (CSR)	Breakaway I rated A (CSCR)
				RPM	Eff%	A		
0.25 (0.18)	2	3000	63 / AL	2820	56	1.6	3.3	3.5
	4	1500	63 / AL	1360	55	1.5	3.3	3.5
	6	1000	71 / AL	880	51.5	1.5	3.1	3.3
0.33 (0.25)	2	3000	63 / AL	2820	59	1.9	3.7	3.8
	4	1500	71 / AL	1380	63	1.8	3.7	3.8
	6	1000	71 / AL	880	59	1.9	3.0	3.3
0.50 (0.37)	2	3000	71 / AL	2840	71	2.3	4.6	4.9
	4	1500	80 / AL	1390	67	2.5	4.5	4.7
	6	1000	80 / AL	890	64	2.5	3.6	4.0
0.75 (0.55)	2	3000	71 / AL	2850	72	3.5	4.6	4.9
	4	1500	80 / AL	1400	70	3.6	4.9	4.9
	6	1000	80 / AL	900	65	3.7	3.1	3.7
1.00 (0.75)	2	3000	80 / AL	2855	72.5	4.5	4.6	4.9
	4	1500	80 / AL	1400	71	4.4	4.5	4.8
	6	1000	90S / AL	910	67	4.5	3.6	4.0
1.50 (1.10)	2	3000	80 / AL	2860	73.5	6.7	4.6	4.9
	4	1500	90S / AL	1410	75	6.5	4.5	4.7
	6	1000	90L/AL/CI	915	69	6.7	3.6	4.0
2.00 (1.50)	2	3000	90S / AL	2865	78	8.4	4.6	4.9
	4	1500	90L/AL/CI	1420	76	8.4	4.6	4.9
	6	1000	100L/AL/CI	920	70	8.4	3.6	4.0
3.00 (2.20)	2	3000	90L/AL/CI	2870	80	12.8	4.7	5.0
	4	1500	100L/AL/CI	1425	79	12.8	4.6	4.9